



▶ ULTRAMAX™ FIT® CHOP/ WET-OUT SYSTEM

The MVP UltraMAX FIT Chop system is one of several MVP systems others compare themselves to.

DESCRIPTION:

▶ SYSTEM FEATURES

The MVP UltraMAX FIT Chop system delivers power, versatility and rugged construction for long lasting use. MVP's Rapid Access Design (RAD) serves you with easy maintenance, and reliable performance.

The best technology in emissions control is the patented FIT (Fluid Impingement Technology). When you use FIT technology, you can be assured you are armed with a state-of-the-art weapon against harmful emissions. The MVP UltraMAX FIT Chop system has very low emissions.

Available in Internal and External Mix Configurations

- Rapid Access Design (RAD) for easy access
- Low Pressure FIT Technology
- Ready for fillers

▶ SPECIFICATIONS

ULTRAMAX™ – STANDARD VOLUME CHOP/WETOUT SYSTEM

Output Capabilities: 3 LBS/MIN – 15 LBS/MIN (1.36 KGS/MIN – 6.80 KGS/MIN)

Avg. Air Consumption with Chopper: 8 CFM (0.23 m³/MIN)

Catalyst % Range: 0.5% to 3% by volume

Available Pump Ratios: 6:1, 11:1 & 15:1

Maximum Air Input Pressure: 100 PSI (7BAR)

ULTRAMAX™ – HIGH VOLUME CHOP/WETOUT SYSTEM

Output Capabilities: 8.5 LBS/MIN – 35 LBS/MIN (3.85 KGS/MIN – 15.87 KGS/MIN)

Avg. Air Consumption with Chopper:

(RESIN) 14CFM (0.4 m³/MIN)

(CHOPPER) 10-20CFM (0.3 - 0.6 m³/MIN)

Catalyst % Range: 0.5% - 2.3% by volume

Available Pump Ratios: 6:1 & 12:1

Maximum Air Input Pressure: 100PSI (7BAR)



▶ OPTIONS

Heaters

- CFH Series

Monitors

- CB-8000

Mixers

- M-AGD

Catalyst Alarms

- CTS-9000

Guns

- TLN Series
- PRO Series
- AT Series

Choppers

- RC Series
- VRC Series

Magnum Industries Europe Ltd. t/a Magnum Venus Products
Official Distributor of MVP Range in the United Kingdom and Ireland

Unit 22a, Navigation Drive, Hurst Business Park,
Brierley Hill, West Midlands, DY5 1UT, UK.

Tel: +44 (0)1384 486222

Email: info@mvpeurope.co.uk

Website: www.mvpeurope.co.uk