

► MINI LINK HYDRAULIC SYSTEM

DESCRIPTION:

► SYSTEM FEATURES

The Mini Link Hydraulic System features a hydraulic meter and cylinder to drive the metering system, delivers an extremely consistent mix/meter of materials at low flow rates, ideal for low & high pressure applications, and more.

- Two magnetic proximity switches for rapid pump reversal change
- Fluid sections are constructed from stainless steel
- Adjustable for ratio variations
- Automatic 1:1 Pro Gun

► SPECIFICATIONS

Ratio:

- Two VHPC-2200: 1:1 TO 3.7:1
- VHPC-2200 & VHPC-3200-ADH: 1.84:1 TO 5.85:1
- VHPC-2200 & VHPC-4200: 4.15:1 TO 13:1

Metering Pumps:

- 120 Volt, 22 amp or 220V single phase, 13.7 amp (voltage must be specified on order)

Air Requirements:

- 20 CFM at 100 psi of clean dry air

Tanks:

- 15-gallon (57 liter) gravity feed (max fill load, 12-gallons each)

Flush Tank:

- 3-gallon (11 liter) pressure tank



► OPTIONS

- In-line Resin Heaters & Heated Hoses

Magnum Industries Europe Ltd. t/a Magnum Venus Products
Official Distributor of MVP Range in the United Kingdom and Ireland

Unit 22a, Navigation Drive, Hurst Business Park, Brierley Hill, West Midlands, DY5 1UT, UK.

Tel: +44 (0)1384 486222

Email: info@mvpeurope.co.uk

Website: www.mvpeurope.co.uk